

## INDUSTRIAL LIGHT

Born To Be Efficient



- ARENA
- ADRENAL
- INTEGRAL
- EXIT















Order NO.	Class	Watt	IP	Angle (°)	CRI	Lumen	Dimmension (mm) (H-W-L)
NILA4424	1	240	65	100	≤85	31200	190 x 280 x 440
NILA5848	1	480	65	100	≤85	62400	190 x 400 x 580























Die cast alminum

**Body Coating: BL.** 












Order NO.	Class	Watt	IP	Angle (°)	CRI	Lumen	Dimmension (mm) (H-W-L)
NLIA2518	1	18	42	120	≤80	1500	25 x 75 x 600
NLIA2536	1	36	42	120	≤80	3000	25 x 75 x 1200
NLIA3536	1	36	42	120	≤80	3060	35 x 75 x 1200





























Order	NO.	Class	Watt	IP	Angle (°)	CRI	Lumen	Dimmension (mm) (H-W-L)
NLII12	250	1	50	65	110	≤80	4000	60 x 90 x 1210
































Order NO.	Class	Watt	IP	Angle (°)	CRI	Lumen	Dimmension (mm) (H-W-L)
NLII1250	1	3	65	180	≤70	200	25 x 200 x 365













MATERIALS: Polycarbonate Body Coating: Wh.







